



LAWN AND GARDEN
QUALITY. DEPENDABILITY.



ATV
INNOVATION. PERFORMANCE.

Lawn & Garden



Twist Link 2 Link & 4 Link

Twist Link ladder style chains (2 link on left) provide added traction for snowblower and garden tractor tires. 2 Link chains have cross chains spaced 2 links apart, while 4 Link chains (on right) are spaced 4 links apart. Packed in cardboard cartons.

TWIST LINK

2 Link Part #	4 Link Part #	Tire Size				2 Link—Wt./Pair (lbs)	4 Link—Wt./Pair (lbs)
3301i		10/10.5x2.75 10.25x3.25	10x3.50 13x4.00-6	14x4.50-6		6	
3308i		12x3				4	
7106i		4.10/3.50x4	3.40/3.00x5			3	
3302i		4.10/3.50x5	12.25x3.50x6	12x3.50x6	4.10/3.50x6	4	
3309i		13x6.50-6	15x5.00-6	5.30/4.50x6		7	
7129i		13x5x6				6	
1301i		4.00x4.80x8				9	
3303i		5.00/5.70x8				10	
3300i		15x6.00-6	16x6.50x8	16x7.50-8		9	
3312i		18x6.50x8	18x8.5-10			10	
3307i	3311i	18x8.50x8				12	8
3305i	3306i	18x9.50x8	20x9x8			12	8
7145i	5320i	20x10.00-8 20x10x8	21x11.00-8 22.5x10.00-8	22x11.00-8 22x11x8	20x10.00-10	21	13
1308i	5318i	20x8x8	20x8.00x10			18	11
5313i		23x7.50x12 6x12	6-14 23x8.50-14	24x8.00-14 24x8.50-14	7.00-14	16	
4300i	4301i	22x10-12 22x9.50-12	23x10-12 23x8.50-12	24x8.50-12 24x9.50-12	8x12	22	13
5308i	5306i	12x12	24x13x12	26x12.00-12	27x12x12	31	18
5307i	5303i	22x11x10	23x10.50-12	23x9.50x12	24x10.50-12	24	15
5300i	5301i	25x10-8	24x12-12			24	15
1307i	1309i	25x8.50-14	27x8.50-15	8x15		28	16
5305i		26x10-12	27x10.50-15	27x12.5-15	27x9.50-15	29	
5323i	5316i	29x12.50-15	29x12-15			44	26
5324i	9100i	31x15.50-15	33x12.50-15			60	35
1311i	1310i	8x16				32	20

ADJUSTERS FOR ATV AND LAWN & GARDEN CHAINS.

Part #	Description	Package Quantity	Weight (lbs)
0271i	Spring Adjuster for ATV/Lawn and Garden, Rim sizes under 10"	1	1
0270i	Spring Adjuster for ATV/Lawn & Garden, Rim sizes of 10" and larger	1	1.5



Twist Link Snow Hog

Snow Hog chains are a twist link ladder design with 2 link spacing. They are built for deep lug tires. Packed in cardboard cartons.

SNOW HOG

Part #	Tire Size		Wt./Pair (lbs)
3302SH	4.10x3.50x6		9
7129SH	13x5x6	14x4.00x6	10
1556SH	15x5.00-6		14
1301SH	4.00x4.80x8		14
3300SH	16x6.50x8	16x7.50-8	16



SPRING TIRE CHAIN ADJUSTER

Chain adjusters keep the chains tight and in place, maximizing the life of the chains. Adjusters are recommended to provide the best performance of the chain. Adjusters mount to the side chain on the outside of the tire. One pair per set is recommended.



ATV



V-Bar 2 Link & 4 Link

V-Bar Reinforced ATV traction chains feature welded V-Bars on the twist link, case hardened cross chains for added traction and durability. 2 Link (on left) chains have cross chains spaced 2 links apart, while 4 Link chains (on right) are spaced 4 links apart. Packed in cardboard cartons.

V-BAR REINFORCED

2 Link Part #	4 Link Part #	Tire Size				2 Link Wt/Pair (lbs)	4 Link Wt/Pair (lbs)
ATV320-2	ATV320	20x10.00-8	22x11x8	22x10x9	23x8-11	25	14
		20x10x8	22x9.00-8	22x10x10			
		22x10-8	25x11x8	22x11x10			
		22x11.00-8	20x10-9	22x8x11			
ATV321-2	ATV321	22x11x9	23.5x8-11	25x8-11	25x8x12	26	16
		23x10x10	24x10x11	23x10-12	205/80-12		
		24x11x10	24x8-11	24x8.00-12			
		25x8-10	24x9x11	24x9x12			
ATV322-2	ATV322	22x12-8	25x13-9	25x11x10	25x10x12	29	19
		24x11x8	23x11-10	25x12x10	25x13.5x12		
		24x11x9	24x11.5x10	24x11-11	26x9-12		
		24x13x9	24x12-10	23x10.50-12	270/60-12		
		25x12x9	25x10x10	24x11.00-12			
ATV323-2	ATV323	25x13.50-9	26x11-12	27x11-12	27x12-14	31	21
		26x10.5x12	26x12.00-12	27x12x12			



V-Bar Diamond® Aggressive Traction

V-Bar Reinforced Diamond® pattern ATV traction chains feature welded V-Bars on the twist link & case hardened diamonds for added traction and durability. Comes with boomer end fasteners for easy tightening. Packed in cardboard cartons.

V-BAR DIAMOND®

Part #	Tire Size				Wt per Pair (lbs)
ATV1	22x11.00-8	22x10x10	23x8-11	23x10.50-12	24
	22x11x8	22x11x10	24x10x11	23x10-12	
	22x10x9	23x10x10	24x9x11	24x9x12	
	22x11x9	23x8-10	205/80-12		
ATV2	24x11x8	25x13-9	25x12x10	270/60-12	26
	25x11x8	24x11.5x10	25x10x12	26x8-14	
	24x11x9	24x11x10	26x8-12	26x9-14	
	24x13x9	25x10x10	26x9.5-12		
	25x12x9	25x11x10	26x9-12		
ATV3	25x11x12	26x12.00-12	26x10-14	27x12-14	28
	25x13.5x12	27x10x12	26x11-14	27x9-14	
	26x10.5x12	27x11-12	26x12-14		
	26x10-12	27x12x12	27x10-14		
	26x11-12	27x9-12	27x11-14		



Diamond® Studded Superior Traction

Diamond® Studded ATV chains are for the most demanding traction applications. Two robotically welded studs on every other link provide extremely aggressive traction. Diamond® pattern allows for a smooth ride. Comes with boomer end fasteners for easy tightening. Packed in cardboard cartons.

DIAMOND® STUDDED

Part #	Tire Size				Wt per Pair (lbs)
ATV605i	22x11.00-8	22x10x10	23x8-11	23x10.50-12	27
	22x11x8	22x11x10	24x10x11	23x10-12	
	22x10x9	23x10x10	24x9x11	24x9x12	
	22x11x9	23x8-10	205/80-12		
ATV610i	24x11x8	25x13-9	25x12x10	270/60-12	29
	25x11x8	24x11.5x10	25x10x12	26x8-14	
	24x11x9	24x11x10	26x8-12	26x9-14	
	24x13x9	25x10x10	26x9.5-12		
	25x12x9	25x11x10	26x9-12		
ATV615i	25x11x12	26x12.00-12	26x10-14	27x12-14	30
	25x13.5x12	27x10x12	26x11-14	27x9-14	
	26x10.5x12	27x11-12	26x12-14		
	26x10-12	27x12x12	27x10-14		
	26x11-12	27x9-12	27x11-14		

MAXI GRIP™

- A superior traction option for equipment with low clearance tolerances
- Easy to install
- Extremely durable
- Use them season after season

SCREW IN ICE STUDS FOR OFF-ROAD & WORK VEHICLES



••••• Carbide tip for durability and superior traction
••• Hexagonal head for application and removal with installation tool
••• Carbide tip is cemented the full depth of the head
••• Hardened and galvanized screw
••••• Coarse threads keep the MaxiGrip™ stud in tire




	HM15	HM18	HM18R
ATV	*	*	
Snowmobile	*	*	*
Motocross/enduro	*		*
Mini Tractor	*	*	
Forklift	*	*	
Snow Groomer		*	
Lawn and Garden	*	*	



YOUR LOCAL DEALER

www.chainandcable.com

International Chain and Cable is a division of Wallingford's Inc.



MARKETED WORLDWIDE by

Wallingford's Inc.
1010 Kennedy Memorial Drive
Oakland, ME USA 04963

207 465 9575 | 800 323 3708
Fax: 207 465 9601

www.wallingfords.com
info@wallingfords.com



WALLINGFORD'S INC.